

Technical Data Sheet

THINNER FOR EPOXY PRIMERS



PRODUCT DESCRIPTION

Thinner for epoxy primers is a mixture of specially combined organic solvents. It is dedicated for Sea-Line epoxy primer. It allows to get final product of clearly defined parameters, provides proper application, leveling and curing. Detailed ratios for each product are given on TDS.

PRODUCT INFORMATION

COLOR	transparent
DENSITY	0,853kg/l
METHODE OF APPLICATION	Paint, brush, spray

INSTRUCTION FOR USE

Thinner is not sell in set with primer. First mix base with hardener keeping mixing proportion, than add thinner in proper proportion –check TDS for specific epoxy primer.

STORAGE AND SAFETY INFORMATION

SHELF LIFE	12 months from production date
STORAGE	Product components should be stored in tightly sealed containers, in a temperature of 10-25°C, away from sources of fire, heat and sunlight. Close container tightly immediately after each use. Store in a dry place and keep sealed cans until use.

HSE CONDITIONS	Please follow safety instructions from the Safety Data Sheet for hazardous chemical and follow workplace safety laws. The general rule is to avoid contact of the product with the skin and eyes. When product is used in a small, closed spaces you must provide forced ventilation. It is also recommended that you protect your respiratory system, eyes, and skin. Special care should be taken in the area of fire protection and explosion hazards. Notice ! Always follow all precautionary, health and safety notice on the Safety Data Sheet and container labels.
----------------	--

DISCLAIMER	All data in this document have been prepared for informational purpose only. We can not take responsibility for the results of user actions over which we have no control. The user is responsible for making the control sample and determining the suitability of the product for specific, individual applications. Company Troton Sp. z o.o. does not take responsibility for any damage, or loss of profits associated with the improper use of the products. All information is based on scrupulous laboratory research and many years of experience. Our position of market leadership does not free us from constant quality control of our products. However, we do not accept responsibility for the effects of improper use or storage of our products, or the effects of using our products in any way contrary to the standard of good workmanship.
------------	--

QUALITY GUARANTEE	Production, quality control and the realization of deliveries fulfill the demands of ISO 9001 and 14001 standards.
-------------------	--